

846 Inventory Inquiry/Advice

Functional Group ID=**IB**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Inventory Inquiry/Advice Transaction Set (846) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used in the following ways: (1) for a seller of goods and services to provide inventory information to a prospective purchaser, with no obligation to the purchaser to acquire these goods or services; (2) for a representative of a seller of goods and services to supply inventory information to that seller; (3) for one location to supply another location with inventory information; and (4) for an inquiry as to the availability of inventory with no obligation on the seller of goods and services to reserve that inventory.

Notes:

- 1. Losing Item Mangers (LIMs) use this transaction set to notify the distribution depot that ownership of stored wholesale assets has transferred to the Gaining Item Manger (GIM) and to request asset information. Distribution depots use this transaction set to report asset information to the LIM.*
- 2. Use a single occurrence of this transaction set to exchange transactions between a single LIM and a single or multiple distribution depots, or between a single distribution depot and a single or multiple LIMs. Use one occurrence of this transaction set to transmit a single or multiple transactions.*
- 3. Users operating under the Defense Logistics Management System (DLMS) must reference the Unit of Issue and Purchase Unit Conversion Table which can be found on the National Institute of Standards and Technology (NIST) World Wide Web site.*

Heading:

	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
Must Use	010	ST	Transaction Set Header	M	1		
Must Use	020	BIA	Beginning Segment for Inventory Inquiry/Advice	M	1		
Not Used	040	CUR	Currency	O	1		
Not Used	050	DTM	Date/Time Reference	O	10		
Not Used	060	REF	Reference Identification	O	12		
Not Used	070	PER	Administrative Communications Contact	O	3		
Not Used	075	MEA	Measurements	O	20		
LOOP ID - N1						5	
Must Use	080	N1	Name	O	1		
Not Used	090	N2	Additional Name Information	O	2		
Not Used	100	N3	Address Information	O	2		
Not Used	110	N4	Geographic Location	O	1		

846S - Inventory Inquiry/Advice (LR Storage Transfer/Order/Reply)

Not Used	120	REF	Reference Identification	O	12
Not Used	130	PER	Administrative Communications Contact	O	3
LOOP ID - LM					10
Must Use	140	LM	Code Source Information	O	1
Must Use	150	LQ	Industry Code	M	100

Detail:

	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
LOOP ID - LIN							10000
Must Use	010	LIN	Item Identification	M	1		
Not Used	030	PID	Product/Item Description	O	200		
Not Used	040	MEA	Measurements	O	40		
Not Used	050	PKG	Marking, Packaging, Loading	O	25		
	100	DTM	Date/Time Reference	O	10		
Not Used	110	CTP	Pricing Information	O	25		
Not Used	120	CUR	Currency	O	1		
Not Used	130	SAC	Service, Promotion, Allowance, or Charge Information	O	25		
Must Use	140	REF	Reference Identification	O	>1		
Not Used	150	PER	Administrative Communications Contact	O	3		
Not Used	220	SDQ	Destination Quantity	O	500		
Not Used	230	MAN	Marks and Numbers	O	1		
Not Used	235	UIT	Unit Detail	O	5		
Not Used	240	CS	Contract Summary	O	1		
Not Used	250	DD	Demand Detail	O	>1		
Not Used	255	G53	Maintenance Type	O	1		
Not Used	256	PCT	Percent Amounts	O	>1		
Not Used	257	LDT	Lead Time	O	12		
LOOP ID - LM							10
Not Used	260	LM	Code Source Information	O	1		
Not Used	270	LQ	Industry Code	M	100		
LOOP ID - SLN							1000
Not Used	280	SLN	Subline Item Detail	O	1		
Not Used	290	PID	Product/Item Description	O	200		
Not Used	300	MEA	Measurements	O	40		
Not Used	310	PKG	Marking, Packaging, Loading	O	25		
LOOP ID - MAN							100
Not Used	312	MAN	Marks and Numbers	O	1		
Not Used	314	MEA	Measurements	O	40		
LOOP ID - QTY							99
	320	QTY	Quantity	O	1		
Not Used	330	UIT	Unit Detail	O	12		
Not Used	340	MEA	Measurements	O	25		
Not Used	350	LDT	Lead Time	O	12		
Not Used	355	DTM	Date/Time Reference	O	10		

846S - Inventory Inquiry/Advice (LR Storage Transfer/Order/Reply)

			LOOP ID - SCH			25	
Not Used	360	SCH	Line Item Schedule	O	1		
Not Used	370	MEA	Measurements	O	25		
			LOOP ID - LM			>1	
	375	LM	Code Source Information	O	1		
Must Use	376	LQ	Industry Code	M	100		
Not Used	380	LS	Loop Header	O	1		
			LOOP ID - REF			>1	
Not Used	390	REF	Reference Identification	O	1		n1
Not Used	400	DTM	Date/Time Reference	O	>1		
Not Used	410	N1	Name	O	1		
			LOOP ID - LM			10	
Not Used	420	LM	Code Source Information	O	1		
Not Used	430	LQ	Industry Code	M	100		
Not Used	440	LE	Loop Trailer	O	1		
			LOOP ID - N1			200	
Must Use	450	N1	Name	O	1		
Not Used	460	N2	Additional Name Information	O	2		
Not Used	470	N3	Address Information	O	2		
Not Used	480	N4	Geographic Location	O	1		
Not Used	490	REF	Reference Identification	O	12		
Not Used	500	PER	Administrative Communications Contact	O	3		

Summary:

	<u>Pos.</u>	<u>Seg.</u>	<u>Name</u>	<u>Req.</u>	<u>Max.Use</u>	<u>Loop</u>	<u>Notes and</u>
	<u>No.</u>	<u>ID</u>		<u>Des.</u>		<u>Repeat</u>	<u>Comments</u>
Not Used	010	CTT	Transaction Totals	O	1		n2
Must Use	020	SE	Transaction Set Trailer	M	1		

Transaction Set Notes

1. The REF loop conveys serial number, lot number, and inventory data.
2. Number of line items (CTT01) is the accumulation of number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (QTY02) of each QTY segment.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ST01	143	Transaction Set Identifier Code	M ID 3/3
			Code uniquely identifying a Transaction Set	
			846 X12.28 Inventory Inquiry/Advice	
Must Use	ST02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>A unique number assigned by the originator of the transaction set, or the originator's application program.</i>	

Segment: **BIA** Beginning Segment for Inventory Inquiry/Advice
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of an Inventory Inquiry/Advice Transaction Set
Syntax Notes:
Semantic Notes:

- 1 BIA03 identifies the number of the inquiry/advice that is transferred.
- 2 BIA04 identifies the date of the inquiry/advice that is transferred.
- 3 BIA05 identifies the time of the inquiry/advice that is transferred.

Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
Must Use	BIA01	353	Transaction Set Purpose Code	M ID 2/2
			Code identifying purpose of transaction set	
			00 Original	
			77 Simulation Exercise	
			<i>Use to identify a simulated mobilization exercise transaction set. Activities initiating simulated mobilization exercises must ensure complete coordination with all activities involved. All transaction set recipients must use extreme caution to ensure that individual transactions do not process as action documents which affect accountable records.</i>	
Must Use	BIA02	755	Report Type Code	M ID 2/2
			Code indicating the title or contents of a document, report or supporting item	
			PK Storage Information Inquiry	
			<i>Use to identify a Logistics Reassignment (LR) storage ownership transfer order.</i>	
			TQ Storage Information Advice	
			<i>Use to identify an LR storage ownership transfer reply.</i>	
Must Use	BIA03	127	Reference Identification	M AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
			<i>Use Code "Z" for this data element to satisfy mandatory X12 syntax requirements.</i>	
Must Use	BIA04	373	Date	M DT 6/6

Date (YYMMDD)

This date is the date of transaction set preparation. This date corresponds to the Universal Time Coordinate (UTC).

BIA05 337 Time O TM 4/8

Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

1. Express the originating activity's time of transaction set preparation in UTC.

2. Express time in a four-position (HHMM) format.

Not Used BIA06 306 Action Code O ID 1/2

Code indicating type of action

Segment: **N1** Name
Position: 080
Loop: N1 Optional (Must Use)
Level: Heading
Usage: Optional (Must Use)
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2 N105 and N106 further define the type of entity in N101.
Notes: *Must use the 1/N1/080 loop to identify the organization originating the transaction set.*

Data Element Summary

	Ref.	Data			Attributes
	Des.	Element	Name		
Must Use	N101	98	Entity Identifier Code		M ID 2/2
			Code identifying an organizational entity, a physical location, or an individual		
			<i>Use only one of code SB or ZN.</i>		
			SB	Storage Area	
				<i>Use to identify a depot or other storage activity.</i>	
			ZN	Losing Inventory Manager	
				The organization losing management responsibility for an individual item of supply	
Not Used	N102	93	Name		X AN 1/35
			Free-form name		
Must Use	N103	66	Identification Code Qualifier		X ID 1/2
			Code designating the system/method of code structure used for Identification Code (67)		
			1	D-U-N-S Number, Dun & Bradstreet	
			9	D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
			10	Department of Defense Activity Address Code (DODAAC)	
			M4	Department of Defense Routing Identifier Code (RIC)	
				An integral and predetermined participant in an established logistical system performing general logistic control, distribution, and storage functions	

Must Use	N104	67	Identification Code	X	AN 2/20
			Code identifying a party or other code		
Not Used	N105	706	Entity Relationship Code	O	ID 2/2
			Code describing entity relationship		
Must Use	N106	98	Entity Identifier Code	O	ID 2/2
			Code identifying an organizational entity, a physical location, or an individual		

FR

Message From

Must use with the appropriate 1/N101/080 code to indicate the organization cited in N104 is originating the transaction set.

Segment: **LM** **Code Source Information**
Position: 140
Loop: LM Optional (Must Use)
Level: Heading
Usage: Optional (Must Use)
Max Use: 1
Purpose: To transmit standard code list identification information
Syntax Notes:
Semantic Notes:
Comments: 1 LM02 identifies the applicable industry code list source information.
Notes: *Must use this 1/LM/140 loop to identify coded information used in department or agency documentation.*

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LM01	559	Agency Qualifier Code Code identifying the agency assigning the code values DF Department of Defense (DoD)	M ID 2/2
Not Used	LM02	822	Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

Segment: **LQ** **Industry Code**
Position: 150
Loop: LM Optional (Must Use)
Level: Heading
Usage: Mandatory
Max Use: 100
Purpose: Code to transmit standard industry codes
Syntax Notes: 1 If LQ01 is present, then LQ02 is required.
Semantic Notes:
Comments:
Notes: *Use to identify codes, as appropriate, consistent with management information requirements.*

Data Element Summary

	Ref.	Data	Attributes
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	LQ01	1270 Code List Qualifier Code Code identifying a specific industry code list 0 Document Identification Code Codes that subclassify a transaction	O ID 1/3
Must Use	LQ02	1271 Industry Code Code indicating a code from a specific industry code list	X AN 1/30

Segment:	LIN Item Identification
Position:	010
Loop:	LIN Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To specify basic item identification data
Syntax Notes:	<ol style="list-style-type: none"> 1 If either LIN04 or LIN05 is present, then the other is required. 2 If either LIN06 or LIN07 is present, then the other is required. 3 If either LIN08 or LIN09 is present, then the other is required. 4 If either LIN10 or LIN11 is present, then the other is required. 5 If either LIN12 or LIN13 is present, then the other is required. 6 If either LIN14 or LIN15 is present, then the other is required. 7 If either LIN16 or LIN17 is present, then the other is required. 8 If either LIN18 or LIN19 is present, then the other is required. 9 If either LIN20 or LIN21 is present, then the other is required. 10 If either LIN22 or LIN23 is present, then the other is required. 11 If either LIN24 or LIN25 is present, then the other is required. 12 If either LIN26 or LIN27 is present, then the other is required. 13 If either LIN28 or LIN29 is present, then the other is required. 14 If either LIN30 or LIN31 is present, then the other is required.
Semantic Notes:	1 LIN01 is the line item identification
Comments:	<ol style="list-style-type: none"> 1 See the Data Dictionary for a complete list of IDs. 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.
Notes:	<i>Must use the 2/LIN/010 loop to identify the National Stock Number (NSN), transaction number, and inventory information.</i>

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Not Used	LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20
Must Use	LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) FS National Stock Number	M ID 2/2
Must Use	LIN03	234	Product/Service ID Identifying number for a product or service	M AN 1/40
Not Used	LIN04	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X ID 2/2
Not Used	LIN05	234	Product/Service ID	X AN 1/40

			Identifying number for a product or service	
Not Used	LIN06	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN07	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN08	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN09	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN10	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN11	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN12	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN13	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN14	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN15	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN16	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN17	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN18	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN19	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN20	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN21	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN22	235	Product/Service ID Qualifier	X ID 2/2

			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN23	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN24	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN25	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN26	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN27	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN28	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN29	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	
Not Used	LIN30	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234)	
Not Used	LIN31	234	Product/Service ID	X AN 1/40
			Identifying number for a product or service	

Segment: **DTM** Date/Time Reference

Position: 100

Loop: LIN Mandatory

Level: Detail

Usage: Optional

Max Use: 10

Purpose: To specify pertinent dates and times

Syntax Notes: **1** At least one of DTM02 DTM03 or DTM06 is required.
2 If either DTM06 or DTM07 is present, then the other is required.

Semantic Notes:

Comments:

Notes: *Use multiple repetitions of this segment to define unique dates associated with the transaction.*

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	DTM01	374	Date/Time Qualifier		M ID 3/3
				Code specifying type of date or time, or both date and time	
			007	Effective	
				<i>Must use for LR storage ownership transfer order transactions to identify the Effective Transfer Date (ETD); otherwise, do not use.</i>	
			036	Expiration	
				Date coverage expires	
				<i>Use for LR storage ownership transfer order transactions for subsistence items to identify the expiration date; otherwise, do not use.</i>	
			510	Date Packed	
				<i>Use for LR storage ownership transfer order transactions for subsistence items to identify the date packed; otherwise, do not use.</i>	
Must Use	DTM02	373	Date		X DT 6/6
				Date (YYMMDD)	
Not Used	DTM03	337	Time		X TM 4/8
				Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	DTM04	623	Time Code		O ID 2/2
				Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time;	

since + is a restricted character, + and - are substituted by P and M in the codes that follow

	DTM05	624	Century	O N0 2/2
			The first two characters in the designation of the year (CCYY)	
Not Used	DTM06	1250	Date Time Period Format Qualifier	X ID 2/3
			Code indicating the date format, time format, or date and time format	
Not Used	DTM07	1251	Date Time Period	X AN 1/35
			Expression of a date, a time, or range of dates, times or dates and times	

Segment: **REF** **Reference Identification**
Position: 140
Loop: LIN Mandatory
Level: Detail
Usage: Optional (Must Use)
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes: *Must use to identify the transaction number.*

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification TN Transaction Reference Number	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30
Not Used	REF03	352	Description A free-form description to clarify the related data elements and their content	X AN 1/80
Not Used	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O
Not Used	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification	M ID 2/3
Not Used	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/30
Not Used	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification	X ID 2/3
Not Used	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30
Not Used	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification	X ID 2/3
Not Used	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as	X AN 1/30

specified by the Reference Identification Qualifier

Segment: **QTY** Quantity
Position: 320
Loop: QTY Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify quantity information
Syntax Notes:
Semantic Notes:
Comments:
Notes: *Use multiple iterations of the 2/QTY/320 loop when exchanging asset status information to stratify quantities by material classification.*

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	QTY01	673	Quantity Qualifier	M ID 2/2
			Code specifying the type of quantity	
			V1 Retention Quantity	
			<i>Use to identify the retention quantity. For LR storage ownership transfer order transactions this represents the quantity scheduled to be retained by the LIM. For LR storage ownership transfer reply transactions this represents the quantity actually retained by the LIM. Do not use in reply transactions if no corresponding order transaction was received.</i>	
			V2 Available Quantity	
			<i>Use for LR ownership transfer reply transactions to identify the quantity transferred to GIM ownership; otherwise, do not use. To reverse all or part of a previously submitted LR ownership transfer reply, use a minus sign in front of the quantity to be reversed.</i>	
			V3 Transfer Quantity	
			<i>Use for LR storage ownership transfer order transactions to identify the quantity to be transferred to GIM ownership; otherwise, do not use. To reverse all or part of an LR storage ownership transfer order, use a minus sign in front of the quantity to be reversed.</i>	
Must Use	QTY02	380	Quantity	M R 1/15
			Numeric value of quantity	
			<i>Express as a number with no decimals.</i>	

	QTY03	C001	Composite Unit of Measure	O
			To identify a composite unit of measure (See Figures Appendix for examples of use)	
Must Use	C00101	355	Unit or Basis for Measurement Code	M ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
			<i>Use to accommodate legacy system requirements. DLMS users see the Unit of Issue and Purchase Unit Conversion Table for applicable codes.</i>	
Not Used	C00102	1018	Exponent	O R 1/15
			Power to which a unit is raised	
Not Used	C00103	649	Multiplier	O R 1/10
			Value to be used as a multiplier to obtain a new value	
Not Used	C00104	355	Unit or Basis for Measurement Code	O ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00105	1018	Exponent	O R 1/15
			Power to which a unit is raised	
Not Used	C00106	649	Multiplier	O R 1/10
			Value to be used as a multiplier to obtain a new value	
Not Used	C00107	355	Unit or Basis for Measurement Code	O ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00108	1018	Exponent	O R 1/15
			Power to which a unit is raised	
Not Used	C00109	649	Multiplier	O R 1/10
			Value to be used as a multiplier to obtain a new value	
Not Used	C00110	355	Unit or Basis for Measurement Code	O ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00111	1018	Exponent	O R 1/15
			Power to which a unit is raised	
Not Used	C00112	649	Multiplier	O R 1/10
			Value to be used as a multiplier to obtain a new value	
Not Used	C00113	355	Unit or Basis for Measurement Code	O ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	
Not Used	C00114	1018	Exponent	O R 1/15
			Power to which a unit is raised	
Not Used	C00115	649	Multiplier	O R 1/10
			Value to be used as a multiplier to obtain a new value	

Segment: **LM** **Code Source Information**
Position: 375
Loop: LM Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To transmit standard code list identification information
Syntax Notes:
Semantic Notes:
Comments: 1 LM02 identifies the applicable industry code list source information.
Notes: *Use the 2/LM/375 loop to identify coded information maintained in department or agency documentation.*

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LM01	559	Agency Qualifier Code Code identifying the agency assigning the code values DF Department of Defense (DoD)	M ID 2/2
Not Used	LM02	822	Source Subqualifier A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

Segment: **LQ** Industry Code
Position: 376
Loop: LM Optional
Level: Detail
Usage: Mandatory
Max Use: 100
Purpose: Code to transmit standard industry codes
Syntax Notes: 1 If LQ01 is present, then LQ02 is required.
Semantic Notes:
Comments:
Notes: *Use to identify codes, as appropriate, consistent with management information requirements.*

Data Element Summary

Ref.	Data			
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>	
Must Use	LQ01	1270 Code List Qualifier Code	O ID 1/3	
		Code identifying a specific industry code list		
		<i>Use one of codes 99 or A1 (but not both) as appropriate.</i>		
		83 Supply Condition Code		
		Classifies material by readiness for issue and use, describes actions underway to change the status of material, or identifies material as excess or not serviceable		
		87 Subsistence Type of Pack Code		
		A certain level of protection from the packing or outside shipping container for perishable and nonperishable subsistence items		
		<i>Use for subsistence items to identify subsistence type of pack information.</i>		
		99 Purpose Code		
		Codes that inform the material owner why an inventory balance is being reserved		
		A1 Ownership Code		
		Items included in the inventory records of an organization that is not the owner of the items		
Must Use	LQ02	1271 Industry Code	X AN 1/30	
		Code indicating a code from a specific industry code list		

Segment:	N1 Name
Position:	450
Loop:	N1 Optional (Must Use)
Level:	Detail
Usage:	Optional (Must Use)
Max Use:	1
Purpose:	To identify a party by type of organization, name, and code
Syntax Notes:	<ol style="list-style-type: none"> 1 At least one of N102 or N103 is required. 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:	
Comments:	<ol style="list-style-type: none"> 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. 2 N105 and N106 further define the type of entity in N101.
Notes:	<i>Must use this 2/N1/450 loop to identify the organization to receive the transaction.</i>

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		
Must Use	N101	98 Entity Identifier Code	M ID 2/2
		Code identifying an organizational entity, a physical location, or an individual	
		<i>Use only one of codes SB or ZN.</i>	
		SB Storage Area	
		<i>Use to identify a depot or other storage activity.</i>	
		ZN Losing Inventory Manager	
		The organization losing management responsibility for an individual item of supply	
		ZP Gaining Inventory Manager	
		The organization assuming management responsibility for an individual item of supply	
		<i>Use only for LR storage ownership transfer order transactions to identify the GIM. Do not use when reversing a previously submitted transaction.</i>	
Not Used	N102	93 Name	X AN 1/35
		Free-form name	
Must Use	N103	66 Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		1 D-U-N-S Number, Dun & Bradstreet	
		9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
		10 Department of Defense Activity Address Code (DODAAC)	

M4

Department of Defense Routing Identifier Code (RIC)

An integral and predetermined participant in an established logistical system performing general logistic control, distribution, and storage functions

Must Use	N104	67	Identification Code	X	AN 2/20
			Code identifying a party or other code		
Not Used	N105	706	Entity Relationship Code	O	ID 2/2
			Code describing entity relationship		
	N106	98	Entity Identifier Code	O	ID 2/2
			Code identifying an organizational entity, a physical location, or an individual		

TO

Message To

Must use with 2/N101/450 codes SB or ZN to indicate the organization cited in N104 is to receive the transaction.

Segment: **SE** Transaction Set Trailer
Position: 020
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:**Semantic Notes:**

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	Number of Included Segments	M N0 1/10
			Total number of segments included in a transaction set including ST and SE segments	
Must Use	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>Cite the same number as the one cited in ST02.</i>	